

WC-8 — USER'S MANUAL

Krzysztof Mazur

Features

- 8 isolated binary inputs
- 24 V, 110 V or 220 V input voltage
- BUSMAT bus

1 Introduction

The WC-8 is an optically isolated 8 digital inputs card with a BUSMAT bus interface.

The WC-8 card is configured by four jumpers that selects four least significant I/O port address bits. Each device must have an unique address on a single BUSMAT bus. Older cards have only one jumper.

1.1 New revisions

This is the revision 0.0 of this specification. The first number is the major revision number. The major revision number identifies the hardware revision. The second number is the minor revision. This number identifies the version of the documentation of for the same hardware.

Latest revision of this document is available at <http://www.microster.pl/doc/wc8>.

1.2 Copyright

Copyright © 2014 Krzysztof Mazur.

This document is licensed under a Creative Commons Attribution-Share Alike 3.0 Unported License.

2 Ordering guide

The WC-8 card is available in the following versions:

Model	Bus	No. Inputs	Input voltage
WC8-24	BUSMAT	8	24 V DC
WC8-110	BUSMAT	8	110 V DC
WC8-220	BUSMAT	8	24 V DC

3 Technical specifications

Bus interface	BUSMAT
Power supply voltage	5 V \pm 5%
Number of inputs	8
Inputs type	DC
Inputs current flow direction	sink
Inputs voltage	24 V or 110 V or 220 V
Inputs voltage tolerance	\pm 35%
Inputs current	3 mA to 6.5 mA
Inputs isolation	\geq 1000 V

3.1 Absolute Maximum Ratings

Parameter	Min	Max	Unit
Supply voltage	-0.5	6.0	V
Input voltage			
24 V	0	32	V
110 V	0	150	V
220 V	0	300	V
Operating temperature	5	60	°C
Storage temperature	-40	85	°C

3.2 Digital inputs recommended operating conditions

Parameter	Min	Typ	Max	Unit
24 V Low-level input voltage	0	0	4	V
24 V High-level input voltage	26	24	30	V
110 V Low-level input voltage	0	0	20	V
110 V High-level input voltage	72	110	150	V
220 V Low-level input voltage	0	0	40	V
220 V High-level input voltage	145	220	300	V

3.3 I/O connector

The WC-8 card I/O connector is presented in Figure 1.

Pin	Description
1	GND
2	GND
3	Binary Input 0
4	Binary Input 1
5	Binary Input 2
6	Binary Input 3
7	Binary Input 4
8	Binary Input 5
9	Binary Input 6
10	Binary Input 7

Figure 1: WC-8 I/O connector.

4 Host interface

The WC-8 card is visible from host as a single I/O port on a BUSMAT bus. The I/O port address is configurable by jumpers in 0xfd80 to 0xfd8f range.

4.1 Binary Input Register

I/O address	0xfd80 to 0xfd8f
Width	8 bit
Type	RO
Reset value	—

7	6	5	4	3	2	1	0
D7	D6	D5	D4	D3	D2	D1	D0
RO	RO	RO	RO	RO	RO	RO	RO

Binary Input Register Bit Descriptions

Bit	Name	Description
7-0	Dn	Digital Input n value. The Dn bit shows the negated logical value of n-th input signal. The bit value is equal to 0 if the voltage is applied to digital input. It is equal to 1 otherwise.